



#0650

## ConSeal

### CONCRETE CURING & SEALING COMPOUND

---

#### DESCRIPTION:

CONSEAL is a water-based curing and sealing compound. It is resistant to yellowing from sunlight exposure, VOC compliant, nonflammable and ready to use. When used as a curing compound it helps control hydration of the cement by preventing rapid loss of moisture through the surface of newly place concrete. As a sealer on concrete, exposed aggregate concrete, and other decorative concretes, CONSEAL is designed to protect and give a “wet look”.

#### WHAT DOES IT DO?

CONSEAL is used on most horizontal and vertical concrete and masonry surfaces, exterior and interior. Typically, applications include stamped concrete, driveways, patios, garages and commercial buildings. CONSEAL is excellent for sealing and dust proofing an older concrete warehouse floor. Its low odor makes it ideal for indoor application in offices, hospitals and schools. It offers outstanding resistance to dirt and attack by air pollutants.

#### HOW IS IT USED?

##### Open (bare) Concrete Floors:

Scrub floor using Grime Buster or Safe Solution at 6oz/gl of water. Rinse floor thoroughly with water. Etch concrete by applying Lime Delete and allow to dry. Apply 3 thin coats of CONSEAL with a flat mop, allowing 1 hour between applications. The floor can be opened to light foot traffic after 4 hours and normal foot traffic after 16-24 hours.

##### Previously Coated Concrete Floors:

Scrub floor to remove all old wax or finishes, using Grime Buster or Safe Solution. Rinse floor thoroughly with water and allow to dry. Apply 3 thin coats of CONSEAL with a flat mop, allowing 1 hour between applications. The floor can be opened to light foot traffic after 4 hours and normal foot traffic after 16-24 hours. For floors sealed with coatings other than CONSEAL, clean the floors as directed and apply a small test patch of CONSEAL to check proper adhesion. Apply the coating as directed.

##### Exterior Concrete Use:

Apply CONSEAL in a uniform, continuous film by sprayer, short napped roller, brush or push broom. Freshly placed concrete: Apply a full even coat of CONSEAL. Use an applicator or roller to pick up puddles or excess material from the surface. A second coat may be applied depending upon the desired surface gloss. A delay of 24 hours is recommended before application of the second coat.

#### PACKAGING:

CONSEAL is available in 1 gallon, 5 gallons & 55 gallon drums.

10/01/2017