

Solutions for a Cleaner Environment

seeks, CAPTURES AND inactivates indoor pathogens.

CHANGE IS IN THE AIR.

PureAir 750+ Wall Mount STAT Unit

Improving Indoor Air Quality & Creating a Healthier Environment with Continuous Air Purification



Continuous Purification



Sized for Multiple Locations



24/7 Odor & Particulate Reduction



No Ductwork Required Easily Mounts to Wall



Wide List of Applications



Applications:

- Workshops
- Offices
- Schools
- Day Care Facilities
- Nursing Homes
- Salons
- Veterinary Clinics
- Motor Coaches
- Public Restrooms

And More!



Providing continuous air purification, this permanently mounted unit is perfect for spaces without HVAC duct access. pureAir 750+ Wall Mount features the same active air purification technology developed and used by NASA.



Active Radiant Catalysis (ARC[®]), this proprietary photocatalytic oxidation (PCO) technology uses energy to activate a catalyst, turning moisture into products that continuously clean your space.

Features & Specifications:

UNIT:

Dimensions: 11.92" H x 9.72" W x 3.64" D Metric: 303mm H x 247mm W x 93mm D Weight: 3.3lbs (1.5kg) Materials: Powder Coated Aluminum Unit Warranty: 2 Year Manufacturer's Warranty

TECHNOLOGIES:

- ★ Active Radiant Catalysis (ARC[®]) Our Proprietary Form of Photocatalytic Oxidation
- ★ Bipolar Ionization Module (BPI)
- * Activated Oxygen (Ozone) Optional



Advanced Oxidation Processes (AOPs) are propelled out into your space to hunt down particulates. At the same time, negative ions go out and charge particles such as dust, pollen and pet dander, causing them to drop out of your breathing space.



With a reactive surface area more than 16x greater than the competition, pureAir 750+ Wall Mount continuously purifies your space. The result is the reduction of allergens from pets, pollen, and smoke, as well as odors from mold, mildew, and more.

POWER:

Input Voltage: 24VDC Operating Voltage 24VDC Supply Power: 120-240VAC | 17W Operating Power: 24VDC | .67A

PERFORMANCE:

Airflow: 70 CFM Optional Ozone Output: < 0.05ppm Coverage: up to 750 ft2

w/ Ozone Item #: STAT w/o Ozone Item #: 1X5853

www.alco-chem.com

NORTH: 45 N Summit Street, Akron, OH 44308 | Hours: M-F, 8:00-4:30 | PH: 330.253.3535 | 1.800.589.2526 SOUTH: 1303 Park Avenue SW, Canton, OH 44706 | Hours: M-F, 8:00-4:30 | PH: 330.833.8551 | 1.800.437.5248